

RENDIMIENTO STANDARD DE RODILLOS									
Modelo	Potencia H.P.	Capacidad Tn	Tipo de Trabajo	Costa	Sierra			Selva	
					Hasta 2300 m.	2300 a 3800 m.	Más de 3800 m.		
<b><u>Autopropulsado</u></b>									
CA-15Liso	101	6.58	Compactación Material Suelto (m3/día)	1,300.00	1,290.00	1,080.00	980.00	1,000.00	
CA-15 P									
Pata Cabra	108	7.40		1,140.00	1,110.00	930.00	850.00	1,150.00	
CA-25Liso	127	9.00		1,700.00	1,670.00	1,400.00	1,270.00	1,290.00	
CA-25D Liso	125	9.40		1,700.00	1,670.00	1,400.00	1,270.00	1,290.00	
CA-25 P									
(Pata Cabra)	125	11.10		1,470.00	1,440.00	1,210.00	1,100.00	1,500.00	
CC-43 Tandem	140	10.10		1,490.00	1,460.00	1,220.00	1,110.00	1,120.00	
CG-11 Tandem	13	1.90		210.00	210.00	170.00	160.00	160.00	
<b><u>Tipo</u></b>									
CH-44 Liso	60	5.00		1,160.00	1,130.00	950.00	860.00	890.00	
CF-44 Pata Cabra	60	5.60		1,010.00	990.00	830.00	750.00	1,020.00	

**Nota:**

Rendimientos estándar por día de 8 horas

**Fuente:**

Libro: "Costos y Tiempos en Carreteras" 1ra Edición 1992

Autor: Ing° Walter Ibañez